

**镍镉电池 Ni-Cd Battery**

Standard Cell (KRM of IEC61951) 标准型电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
1/3AAA50	1.2	50	5	16	3C	210	10.5	15.5	3
4/5AAA320	1.2	320	32	16	3C	65	10.5	38.5	9
AAA300	1.2	300	30	16	3C	60	10.5	44.0	9
1/3AA150	1.2	150	15	16	3C	150	14.5	17.0	7
2/3AA300	1.2	300	30	16	3C	50	14.5	29.0	10
2/3AA350	1.2	350	35	16	3C	50	14.5	29.0	10
2/3AA400	1.2	400	40	16	3C	50	14.5	29.0	11
AA500	1.2	500	50	16	3C	40	14.5	49.0	15
AA600	1.2	600	60	16	3C	40	14.5	49.0	16
AA700	1.2	700	70	16	3C	35	14.5	49.0	17
AA800	1.2	800	80	16	3C	35	14.5	49.0	18
AA900	1.2	900	90	16	3C	35	14.5	49.0	19
AA1000	1.2	1000	100	16	3C	35	14.5	49.0	20
AA1100	1.2	1100	110	16	3C	35	14.5	49.0	21
1/2A700	1.2	700	70	16	3C	40	17.0	28.5	16
4/5A1200	1.2	1200	120	16	3C	35	17.0	43.0	26
A1400	1.2	1400	140	16	3C	30	17.0	50.0	29
4/5SC1200	1.2	1200	120	16	3C	32	23.0	34.0	33
SC1300	1.2	1300	130	16	3C	26	23.0	43.0	38
SC1500	1.2	1500	150	16	3C	25	23.0	43.0	41
SC1800	1.2	1800	180	16	3C	25	23.0	43.0	44
SC2000	1.2	2000	200	16	3C	25	23.0	43.0	46
SC2200	1.2	2200	220	16	3C	25	23.0	43.0	47
1/2C800	1.2	800	80	16	3C	55	26.0	24.0	28
C2500	1.2	2500	250	16	3C	25	26.0	49.0	63
C2800	1.2	2800	280	16	3C	25	26.0	49.0	65
C3000	1.2	3000	300	16	3C	22	26.0	49.0	68
1/2D2500	1.2	2500	250	16	3C	22	33.0	35.5	68
D4000	1.2	4000	400	16	3C	16	33.0	59.5	111
D4500	1.2	4500	450	16	3C	16	33.0	59.5	118
D5000	1.2	5000	500	16	3C	16	33.0	59.5	126
F7000	1.2	7000	700	16	3C	14	33.0	90.0	178
F8000	1.2	8000	800	16	3C	14	33.0	90.0	193

High Temperature Cell (KRMT of IEC61951) 高温型电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
2/3AA300HT	1.2	300	30	16	1C	60	14.5	29.0	10
AA600HT	1.2	600	60	16	1C	35	14.5	49.0	17
AA700HT	1.2	700	70	16	1C	35	14.5	49.0	18
AA750HT	1.2	750	75	16	1C	35	14.5	49.0	18
AA800HT	1.2	800	80	16	1C	35	14.5	49.0	19
AA900HT	1.2	900	90	16	1C	35	14.5	49.0	20
AA1000HT	1.2	1000	100	16	1C	35	14.5	49.0	21
AA1100HT	1.2	1100	110	16	1C	35	14.5	50.0	22
SC1200HT	1.2	1200	120	16	1C	32	23.0	43.0	38
SC1300HT	1.2	1300	130	16	1C	27	23.0	43.0	39
SC1500HT	1.2	1500	150	16	1C	25	23.0	43.0	41
SC1600HT	1.2	1600	160	16	1C	25	23.0	43.0	42
SC1800HT	1.2	1800	180	16	1C	25	23.0	43.0	45
SC2000HT	1.2	2000	200	16	1C	25	23.0	43.0	47
C2200HT	1.2	2200	220	16	1C	25	26.0	49.0	61
C2500HT	1.2	2500	250	16	1C	25	26.0	49.0	64
C2800HT	1.2	2800	280	16	1C	25	26.0	49.0	68
C3000HT	1.2	3000	300	16	1C	25	26.0	49.0	69
1/2D2200HT	1.2	2200	220	16	1C	25	33.0	35.5	67
D4000HT	1.2	4000	400	16	1C	16	33.0	59.5	111
D4500HT	1.2	4500	450	16	1C	16	33.0	59.5	118
D5000HT	1.2	5000	500	16	1C	16	33.0	59.5	126
F7000HT	1.2	7000	700	15	1C	16	33.0	89.5	178

Ultra High Temperature Cell (KRMU of IEC61951) 超高温型电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
AA600GT	1.2	600	60	16	1C	35	14.5	49.0	17
AA700GT	1.2	700	70	16	1C	35	14.5	49.0	18
AA800GT	1.2	800	80	16	1C	35	14.5	49.0	19
AA900GT	1.2	900	90	16	1C	35	14.5	49.0	20
AA1000GT	1.2	1000	100	16	1C	35	14.5	49.0	21
AA1100GT	1.2	1100	110	16	1C	35	14.5	50.0	22
SC1500GT	1.2	1500	150	16	1C	25	23.0	43.0	41
SC1600GT	1.2	1600	160	16	1C	25	23.0	43.0	42
SC1700GT	1.2	1700	170	16	1C	25	23.0	43.0	43
SC1800GT	1.2	1800	180	16	1C	25	23.0	43.0	45
SC2000GT	1.2	2000	200	16	1C	25	23.0	43.0	47
C2200GT	1.2	2200	220	16	1C	25	26.0	49.0	61
C2500GT	1.2	2500	250	16	1C	25	26.0	49.0	64
C2800GT	1.2	2800	280	16	1C	25	26.0	49.0	68
C3000GT	1.2	3000	300	16	1C	25	26.0	49.0	70
D4000GT	1.2	4000	400	16	1C	16	33.0	59.5	113
D4500GT	1.2	4500	450	16	1C	16	33.0	59.5	120

High Rate Discharge Cell (KRX of IEC61951) 高倍率电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
4/5SC1300P	1.2	1300	130	16	10C	18	23.0	34.0	35
SC1300P	1.2	1300	130	16	10C	13	23.0	43.0	38
SC1500P	1.2	1500	150	16	10C	12	23.0	43.0	42
SC1800P	1.2	1800	180	16	10C	12	23.0	43.0	44
SC2000P	1.2	2000	200	16	10C	12	23.0	43.0	46