

镍氢电池 Ni-MH Battery

Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
Consumer Cell - High Top (HRM of IEC61951) 民用尖头电芯									
HAAA500B	1.2	500	50	16	3C	45	10.5	44.5	10
HAAA600B	1.2	600	60	16	3C	45	10.5	44.5	11
HAAA700B	1.2	700	70	16	3C	40	10.5	44.5	12
HAAA800B	1.2	800	80	16	3C	40	10.5	44.5	13
HAAA900B	1.2	900	90	16	3C	40	10.5	44.5	14
HAAA1000B	1.2	1000	100	16	3C	40	10.5	44.5	15
HAAA1100B	1.2	1100	110	16	3C	40	10.5	44.5	15
HAA1300B	1.2	1300	130	16	3C	35	14.5	50.5	21
HAA1500B	1.2	1500	150	16	3C	35	14.5	50.5	23
HAA1600B	1.2	1600	160	16	3C	35	14.5	50.5	24
HAA1800B	1.2	1800	180	16	3C	35	14.5	50.5	26
HAA2000B	1.2	2000	200	16	3C	35	14.5	50.5	27
HAA2200B	1.2	2200	220	16	3C	35	14.5	50.5	28
HAA2400B	1.2	2400	240	16	3C	35	14.5	50.5	30
HAA2500B	1.2	2500	250	16	3C	25	14.5	50.5	31
HAA2600B	1.2	2600	260	16	3C	25	14.5	50.5	31
HC4000B	1.2	4000	400	16	3C	20	26.0	50.5	74
HC4500B	1.2	4500	450	16	3C	20	26.0	50.5	78
H1/2D3500B	1.2	3500	350	16	3C	20	33.0	36.5	76
HD8000B	1.2	8000	800	16	3C	15	33.0	61.5	140
HD9000B	1.2	9000	900	16	3C	15	33.0	61.5	150
Standard Cell - Flat Top (HRM of IEC61951) 平头标准型电芯									
H1/3AAA150	1.2	150	15	16	3C	120	10.5	15.5	4
H2/3AAA300	1.2	300	30	16	3C	65	10.5	29.0	7
H2/3AAA400	1.2	400	40	16	3C	65	10.5	29.0	7
HAAA500	1.2	500	50	16	3C	45	10.5	44.0	10
HAAA600	1.2	600	60	16	3C	45	10.5	44.0	11
HAAA700	1.2	700	70	16	3C	40	10.5	44.0	12
HAAA800	1.2	800	80	16	3C	40	10.5	44.0	13
HAAA900	1.2	900	90	16	3C	40	10.5	44.0	14
H2/3AA600	1.2	600	60	16	3C	48	14.5	29.0	15
H2/3AA700	1.2	700	70	16	3C	48	14.5	29.0	15
H4/5AA1300	1.2	1300	130	16	3C	40	14.5	44.0	20
HAA1200	1.2	1200	120	16	3C	40	14.5	49.0	20
HAA1300	1.2	1300	130	16	3C	40	14.5	49.0	21
HAA1500	1.2	1500	150	16	3C	35	14.5	49.0	23
HAA1600	1.2	1600	160	16	3C	35	14.5	49.0	24
HAA1800	1.2	1800	180	16	3C	35	14.5	49.0	26
HAA2000	1.2	2000	200	16	3C	35	14.5	49.0	27
HAA2200	1.2	2200	220	16	3C	35	14.5	49.0	28
HAA2400	1.2	2400	240	16	3C	35	14.5	50.0	30
H1/2A1200	1.2	1200	120	16	3C	35	17.0	29.0	21
H4/5A2000	1.2	2000	200	16	3C	30	17.0	43.0	31
H7/5A3600	1.2	3600	360	16	3C	28	17.0	67.0	50
HSC2800	1.2	2800	280	16	3C	20	23.0	43.0	52
HSC3000	1.2	3000	300	16	3C	20	23.0	43.0	54
HC4000	1.2	4000	400	16	3C	20	26.0	49.0	74
HC4500	1.2	4500	450	16	3C	20	26.0	49.0	80
H1/2D3500	1.2	3500	350	16	3C	20	33.0	35.5	76
HD8000	1.2	8000	800	16	3C	15	33.0	59.5	145
HD9000	1.2	9000	900	16	3C	15	33.0	59.5	155
High Rate Discharge Cell (HRX of IEC61951) 高倍率电芯									
H4/5A2000P	1.2	2000	200	16	10C	8	17.0	43.0	31
HSC3000P	1.2	3000	300	16	10C	5	23.0	43.0	55
HSC3600P	1.2	3600	360	16	10C	5	23.0	43.5	62

High Temperature Cell (HRMT of IEC61951) 高温型电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
H1/3AAA60HT	1.2	60	6	16	1C	180	10.5	15.5	4
H2/3AAA300HT	1.2	300	30	16	1C	65	10.5	29.0	7
HAAA500HT	1.2	500	50	16	1C	45	10.5	44.0	10
HAAA600HT	1.2	600	60	16	1C	45	10.5	44.0	11
H1/3AA120HT	1.2	120	12	16	1C	150	14.5	17.0	6
H2/3AA500HT	1.2	500	50	16	1C	60	14.5	29.0	13
HAA1100HT	1.2	1100	110	16	1C	35	14.5	49.0	22
HAA1200HT	1.2	1200	120	16	1C	35	14.5	49.0	23
HAA1300HT	1.2	1300	130	16	1C	35	14.5	49.0	24
HAA1500HT	1.2	1500	150	16	1C	35	14.5	50.0	25
HAA1600HT	1.2	1600	160	16	1C	35	14.5	50.0	25
HAA1800HT	1.2	1800	180	16	1C	35	14.5	50.0	26
HSC1500HT	1.2	1500	150	16	1C	25	23.0	43.0	38
HSC2000HT	1.2	2000	200	16	1C	20	23.0	43.0	44
HSC2500HT	1.2	2500	250	16	1C	20	23.0	43.0	50
H7/5SC4000HT	1.2	4000	400	16	1C	20	23.0	60.5	75
HC3500HT	1.2	3500	350	16	1C	25	26.0	49.0	69
HC4000HT	1.2	4000	400	16	1C	20	26.0	49.0	74
HD7000HT	1.2	7000	700	16	1C	15	33.0	59.5	135
HD8000HT	1.2	8000	800	16	1C	15	33.0	59.5	145
Ultra High Temperature Cell (HRMU of IEC61951) 超高温型电芯									
Model	Nominal Voltage (V)	Nominal Capacity (mAh)	Standard charge (CC)		Max. Discharge rate	Max. Internal resistance (mOhm)	Max. Dimensions		Weight approximate (g)
			Current (mA)	Time (hrs.)			Diameter (mm)	Height (mm)	
HAAA500GT	1.2	500	50	16	1C	45	10.5	44.0	10
HAA1100GT	1.2	1100	110	16	1C	35	14.5	49.0	22
HAA1200GT	1.2	1200	120	16	1C	35	14.5	49.0	23
HAA1500GT	1.2	1500	150	16	1C	35	14.5	50.0	25
HSC2000GT	1.2	2000	200	16	1C	20	23.0	43.0	44
HSC2200GT	1.2	2200	220	16	1C	20	23.0	43.0	46
HC4000GT	1.2	4000	400	16	1C	20	26.0	49.0	76
HD6000GT	1.2	6000	600	16	1C	15	33.0	59.5	125
HD7000GT	1.2	7000	700	16	1C	15	33.0	59.5	135